

## Brillensteckscheiben DP 10/16 (Stahl)

- Auslegungsdruck pmax. 10 bar / DP 10, pmax. 16 bar / DP 16
- Berechnungsgrundlage AD Merkblatt B 5
- komplette Stempelung und Abnahmeprüfzeugnis EN 10204 / 3.1B

<b>Standard-Werkstoffe</b>	<b>St 52.3</b>
<b>Technische Lieferbedingungen</b>	DIN 17100
<b>AD-Merkblatt</b>	W 1

<u>Anschluss</u> DN	<u>Anschluss</u> DP	<u>S</u> mm	<u>d1</u> mm	<u>d2</u> mm
25	10	8	68	28
32	10	8	78	37
40	10	8	88	43
50	10	8	102	54
65	10	8	122	70
80	10	8	138	82
100	10	8	158	107
125	10	8	188	131
150	10	8	212	159
200	10	8	268	207
250	10	10	320	260
300	10	12	370	309
400	10	13	482	403
500	10	17	585	492
25	16	8	68	28
32	16	8	78	37
40	16	8	88	43
50	16	8	102	54
65	16	8	122	70
80	16	8	138	82
100	16	8	158	107
125	16	8	188	131
150	16	10	212	159
200	16	10	268	207
250	16	12	320	260
300	16	13	378	309
400	16	18	490	403
500	16	18	610	492

